



SafetyReel G2 hose reels

SafetyReel G2 hose reels

Technical data

Max working pressure (bar)	16 bar
Max working pressure connected (bar)	16 bar
Media	Air/water, Air
Hose variants	C-line
Hose material	PUR/PVC
Min temperature (°C)	-20 °C
Max temperature (°C)	60 °C
Hose type	Straight Braided
Hose color	Blue, Hi-vis green
Max working pressure (MPa)	1.6 MPa
Hose length on reel (m)	20 - 30 m
Reel material	Plastic
Reel type	Closed reel



	Part No.	Category	ID x OD (mm)	Connection Inlet	Connection Outlet
	199112620	Large reel	11.0 x 16.0	R 1/2" Male	R 1/2" Male
	199112621	Large reel	11.0 x 16.0	1/2" NPT Male	1/2" NPT Male
	199112622	Large reel	11.0 x 16.0	eSafe 320 Nipple	eSafe 320 coupling
	199112630	Large reel	11.0 x 16.0	eSafe 320 nipple	eSafe 320 coupling
	199112640	Large reel	13.0 x 18.0	R 1/2" Male	R 1/2" Male
	199112641	Large reel	13.0 x 18.0	1/2" NPT Male	1/2" NPT Male
	199112642	Large reel	13.0 x 18.0	eSafe 320 Nipple	eSafe 320 coupling
	199112643	Large reel	13.0 x 18.0	eSafe 410 Nipple	eSafe 410 coupling

Check with an authorized CEJN distributor for availability and prices. All measurements are in mm. Some part numbers may be subject to minimum order quantities. CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO standards, unless stated otherwise.

	199112650	Large reel	13.0 x 18.0	eSafe 320 Nipple	eSafe 320 coupling
	199112660	Large reel	16.0 x 21.0	R 3/4" Male	R 3/4" Male
	199112662	Large reel	16.0 x 21.0	eSafe 410 Nipple	eSafe 410 coupling
	199112661	Large reel	16.0 x 21.0	3/4" NPT Male	3/4" NPT Male
	199112670	Large reel	16.0 x 21.0	eSafe 410 Nipple	eSafe 410 coupling

Check with an authorized CEJN distributor for availability and prices. All measurements are in mm. Some part numbers may be subject to minimum order quantities. CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO standards, unless stated otherwise.