



Developed for the Data Center industry

Thermal management hoses

Designed to support reliable temperature management, this thermal management hose provides the flexibility and performance needed for modern liquid cooling installations. Built with UL 94 V-0 flame-resistant materials, it ensures safety even in challenging conditions. Its high flexibility and kink-resistant design allow it to navigate tight spaces with ease, helping simplify both installation and ongoing maintenance.



TECHNICAL DATA

Category Thermal management hose
 Max. working pressure..... 10 bar (150 PSI)
 Min. burst pressure..... 40 bar (600 PSI), 4:1 safety factor
 Hose material. EPDM rubber, peroxide-cured, high strength braiding, black
 Media Coolant solutions, Water, Air
 Temperature range -40°C – +100°C (-40°F – +212°F)
 Certifications..... UL94 V-0 flame resistant

Part no.	ID x OD (mm)	ID x OD (inch)	Bend radius (mm)	Weight (kg/m)
19 900 9704	6.4 x 12.0	0.25 x 0.47	40	0.10
19 900 9706	9.5 x 16.0	0.375 x 0.63	50	0.16
19 900 9708	12.7 x 22.0	0.50 x 0.87	70	0.31
19 900 9710	16.0 x 25.2	0.625 x 1.00	85	0.40
19 900 9712	19.0 x 29.7	0.75 x 1.17	100	0.54
19 900 9716	25.4 x 36.5	1.00 x 1.44	130	0.73