Declaration of Compliance

Business Operator	CEJN AB Rattvägen 1 P.O. Box 245 SE-541 25 Skövde Sweden Tel. +46 (0) 500 47 75 00
	Information given in this declaration is based on our current state of knowledge and written confirmation from our suppliers.
Product name	White food safe hose reel for washdown with water.



This DoC applies to the following product	199112242
Materials	POM, PPH, PP, PA66, PUR, NBR and AISI316.
Color	White hose reel with blue CEJN cover and blue hose.

EU Compliance

Reg. (EC) No 1935/2004	In accordance with EU Commission Regulation No 1935/2004, Food Contact Material (FCM). The intended use for the white hose reel mentioned above is to transport water for washdown purposes within the food and beverage industry with unintended contact with food.
Reg. (EC) No. 10/2011	Commission Regulation (EU) No 10/2011 of 14 January 2011 on plastic materials and articles intended to come into contact with food. (Regulation (EU) No 10/2011 and its amendments).
Reg. (EC) No. 2023/2006	Commission Regulation (EC) No 2023/2006 of 22 December 2006 on good manufacturing practice for materials and articles intended to come into contact with food (GMP) as amended.


US FDA Compliance	The composition is compliant for use in food contact applications according to the CFR Title 21 177. 2470 "Polyoxymethylene copolymer" and Titles 21 176.170, 177.1520 and 177.2600. The antioxidants used in Product(s) also comply with the CFR Title 21 178. 2010 "Antioxidants and/or stabilizers for polymers". Any additives that may be present comply with appropriate, specific FDA regulations.
Migration analysis report	We will make the relevant background documentation available to the competent authorities, at their request.
Food contact	The intended use of the white hose reel is for washdown purposes only (mix of water & detergents). Any other use, such as transporting liquid foodstuffs, is not permitted. All plastic materials listed below under 'Materials' are made from food-grade plastic and, according to certificates and documentation from our suppliers, comply with both EU and FDA regulations regarding plastic materials in contact with food.
Min. temperature	5°C (41°F)
Max temperature	60°C (140°F)
Max working pressure	10 bar (1.0 MPa)
General	Equipment should be cleaned and disinfected, as appropriate to its intended use, before use. It is also important to clean and disinfect equipment as appropriate after use, using the appropriate decontamination chemicals, concentrations, times and temperatures. Appropriate equipment decontamination will minimize the risk of microbial growth and cross contamination and will maximize the efficiency and durability of the equipment.

Materials

Outer white housing	Polypropylene (PP).
Hose (Blue)	Polyurethane (PUR). (Please note that the PUR hose has a separate DoC).
Hose connections	AISI316
Stop ball (Dark grey)	Polyamide (PA66) (Please note that the Stop ball has a separate DoC).
Drum (Grey)	Polypropylene Homopolymer (PPH).
Swivel (Black)	Polyoxymethylene (POM).
Connection angle (white)	Polyoxymethylene (POM).
Nipples (Black)	Polyoxymethylene (POM).
Seals (Black)	Nitrile rubber (NBR).
Grease	Cargo Fluor (NSF H1) and soft Paraffin.

Date 11th of November 2026

Made by



Joachim Schröter
Segment Manager – Food & Beverage Industry