

CAD system: Inventor
All rights reserved
This document must not be copied, either completely or in part, without permission. Any infringement will have legal consequences ©



A3

D

C

B


A

D



C

B


A



1 : 1



11	1	Valve	Aluminum Lead Free
10	1	Valve seat	Aluminum Lead Free
9	1	Spring	Stainless Steel
8	1	Spring	Stainless Steel
7	1	Lip seal	NBR
6	1	Quad-Ring	NBR
5	1	O-ring	NBR
4	1	Locking sleeve	Hard. Steel, Zn 8 silver
3	3	Hook	Hard. Steel, Zn-Ni 8 transp.
2	1	Front part	Hard. Steel Zn 8 Silver
1	1	Back part	Steel, Zn 8 Silver
Item	Qty	Description	Material



Product No.	104102004
Nominal flow Ø DN:	7,8 mm
Connection Stroke:	18,9 mm
Max WP Connected:	16 bar
Min BP Connected:	64 bar
Temperature range:	-20°C - +100°C
Connection:	Hose 3/8" 10mm
Sealing material:	NBR

State	Drawn	Checked	Approved	Date
Production	CABLIJA	ALAL	OSJO	2025-02-07
 Coupling 3/8" hose NBR - eSafe		ECO	Former No.	Scale
		002136		2 : 1
Drawing No.			Issue	Sheet
104102004			C	1 /(1)